



(19)

(11) Publication number

Generated Document

PATENT ABSTRACTS OF JAPAN

(21) Application number 08258215

(51) Intl. Cl. G11C 16/02 G11C 16/0

(22) Application date: 30.09.96

(30) Priority:

(43) Date of application
publication: 24.04.98(84) Designated contracting
states:(71) Applicant HITACHI LTD
HITACHI VLSI EN(72) Inventor: KAWAHARA TAKU
SATO HIROSHI
NOZOE ATSUSHI
YOSHIDA KEIICHI
NODA TOSHIFUMI
KUBONO SHIYOU
KOTANI HIROAKI
KIMURA KATSUTAKA


(74) Representative

(54) SEMICONDUCTOR
INTEGRATED CIRCUIT,
AND DATA-PROCESSING
SYSTEM


(57) Abstract:

PROBLEM TO BE SOLVED: To speed up the write operation to a memory by providing a control means with a first mode, in which the change of a threshold voltage of a nonvolatile memory cell is relatively large, and a second mode, in which the change is relatively small.

SOLUTION: The voltage of a write work line of a flash memory FMRY1 is made constant and the write pulse width is increased sequentially. The system is provided with a voltage-applying pulse string generation means 100 for a first write mode (rough write) wherein a memory cell threshold voltage changes by ΔV_{th1} per one write pulse, and a second



write voltage-applying pulse string generation means 101 (highly accurate write) wherein the threshold voltage changes by ΔV_{th2} . The number of pulses for changing the threshold voltage of a memory cell MC is small in the case of ΔV_{th1} than in the case of ΔV_{th2} . Therefore, the number of verification times with the use of the means 100 is smaller than that with the use of the means 101. Since an overhead time is shorter when the number of verification times is smaller, the write time is reduced.



COPYRIGHT: (C)1998,JPO